

BASIC STANDARDS MANUAL |

CONTENT

LOGOTYPE	3
EMBLEM AND TYPORGAPHY RELATION	4
EXCLUSION AREA	8
MINIMUM SIZE	9
COLOURS	1 0
POSITIVE AND NEGATIVE	1 2
SPECIAL APPLICATIONS	1 3
LOGOTYPE AND BACKGROUND RELATION	1 4
TYPORGAPHY	18

LOGOTYPE


Logotype consists of 3D emblem and name of the company designed using the specific font.




Logotype is always used in relations showed here.

Dimension "X" is used to define the distance between emblem and typography. It's equal to the width of letter "C".

The emblem is horizontally centered in relation to textual part of the logotype.





Unallowed applications ...

Any intervention which disrupts the original logotype form is not allowed: unproportional transformation, change of position of basic graphic elements, partial rotation etc.













8

Allowed applications *.

Here described applications are allowed only in certain cases when narrow formats are in question.







FLAGS (100 X 400 cm)






Allowed applications *.

Here described applications are allowed only in certain cases when narrow formats are in question.



FLAGS (100 X 400 cm)




*these applications are used in argeement with agency.

EXCLUSION AREA

Exclusion area is area within which should be no other graphic elements and defines distance to format borders.

Dimension "X" is equal to the width of letter "C".

Exclusion area is 2xX. In certain cases when it is not possible to apply the reduced exclusion area is used.



MINIMUM SIZE

Minimum size of logotype in it's original form is 1.5 cm width.


In case of smaller application positive or negative should be used depending on the background colour. The minmum size is 0.8 cm.











COLOURS

Basic colours are black,
white and yellow-green.
The emblem should be
reproduced in CMYK* and
typographic part in basic
colours combination
depending on the
background.

TESLA CABLES TESLA CABLES TESLA CABLES

*when reducing costs or depending on printing process, reproduction in CMYK is not possible, the emblem should be converted to grayscale mode.

COLOUR DEFINITION

Basic colours are black, white and yellow-green.



POSITIVE AND NEGATIVE

Positive or negative form is used when it is not possible to reproduce the logotype in its basic form.

It depends on the printing process.





SPECIAL APPLICATIONS

The forms of logotype used when it is not possible to reproduce the logotype in its basic form. It depends on the printing process.






LOGOTYPE AND BACKGROUND RELATION (primary form)

Logotype should be used on white, black or yellow-green background as shown here.






LOGOTYPE AND BACKGROUND RELATION (secondary form)

It is allowed to use logotype on other background colours as long as it is recognizable and readable.

When that is not the case the form marked with A is allowed.



LOGOTYPE AND BACKGROUND RELATION (secondary form)

It is allowed to use logotype on other background colours as long as it is recognizable and readable.

When that is not the case the form marked with 1 is allowed.




LOGOTYPE AND BACKGROUND RELATION (secondary form)

If the background is not one of the basic colours (white, black, yellow-green) the logotype is used in forms shown here.

The form that ensures recognizability, readability and corresponds with other graphic elements should be used.

The same applies to using the logotype on photographs.



TYPORGAPHY

Helvetica Neue LT Pro - all typefaces, depending on application.

Ubuntu and Open Sans - all typefaces, depending on application in digital media.

Lorem Ipsum is simply dummy text of the printing and typesetting industry. Lorem Ipsum has been the industry's standard dummy text ever since the 1500s, when an unknown printer took a galley of type and scrambled it to make a type specimen book. It has survived not only five centuries, but also the leap into electronic typesetting, remaining essentially unchanged. It was popularised in the 1960s with the release of Letraset sheets containing Lorem Ipsum passages, and more recently with desktop publishing software like Aldus PageMaker including versions of Lorem Ipsum. Lorem Ipsum is simply dummy text of the printing and typesetting industry. Lorem Ipsum has been the industry's standard dummy text ever since the 1500s, when an unknown printer took a galley of type and scrambled it to make a type specimen book. It has survived not only five centuries, but also the leap into electronic typesetting, remaining essentially unchanged. It was popularised in the 1960s with the release of Letraset sheets containing Lorem Ipsum passages, and more recently with desktop publishing software like Aldus PageMaker including versions of Lorem Ipsum. Lorem Ipsum is simply dummy text of the printing and typesetting industry.

Lorem Ipsum is simply dummy text of the printing and typesetting industry. It was popularised in the 1960s with the release of Letraset sheets containing Lorem Ipsum passages, and more recently with desktop publishing software like Aldus PageMaker including versions of Lorem Ipsum. Lorem Ipsum is simply dummy text of the printing and typesetting industry. It has survived not only five centuries, but also the leap into electronic typesetting, remaining essentially unchanged.

Lorem Ipsum is simply dummy text of the printing and typesetting industry. It was popularised in the 1960s with the release of Letraset sheets containing Lorem Ipsum passages, and more recently with desktop publishing software like Aldus PageMaker including versions of Lorem Ipsum. Lorem Ipsum is simply dummy text of the printing and typesetting industry. It has survived not only five centuries, but also the leap into electronic typesetting, remaining essentially unchanged. It has survived not only five centuries, but also the leap into electronic typesetting, remaining essentially unchanged.