

DOP Document Number: ECCE-09-21

## Standard & product range.

## EYY Circular Conductor

No. of Cores	Size	
1	4 mm <sup>2</sup> to 630 mm <sup>2</sup>	
2	1.5 mm <sup>2</sup> to 50 mm <sup>2</sup>	
3, 4	1.5 mm <sup>2</sup> to 25 mm <sup>2</sup>	
3+E	25+16 mm <sup>2</sup>	
5	1.5 mm <sup>2</sup> to 300 mm <sup>2</sup>	
7	1.5 mm <sup>2</sup> to 10 mm <sup>2</sup>	
14, 19	1.5 mm <sup>2</sup> to 4 mm <sup>2</sup>	
10, 12, 16, 21, 24, 30, 40, 52	1.5 mm <sup>2</sup> to 2.5 mm <sup>2</sup>	
61	1.5	

Traceability of each cable is followed by drum numbers

## Intended Use of Product Type

Supply of electricity in buildings and other civil engineering Works with the objective of limiting the generation and spread of fire and smoke

### **Manufacturer Information**

Manufacturer:

EL SEWEDY CABLES

Office: plot 27, 1st district.5th settlement, new Cairo.

Tel: 72599732-27599733-27599734

Fax: 27599735 P.O.Box:311-post code: 11853

**Factory Address** 

**WWW.ELSEWEDY.COM** 

Factory: 10th of Ramadan City, Industrial Zone, Egypt.

**Tel.:** (2015) 411350 **fax:** (2015)411366 **PO.Box:** 1748 post code: 10505

# System or Systems of Assessment and Verification of Constancy of Performance

System 3

# Notified Body/laboratory

**IMQ** No. 0051

#### Performances Declared

Essential Characteristic	Performance	Harmonized Technical Specification
Reaction to Fire	Eca	
Smoke Production	-	
Flaming Droplets	-	EN 50575:2014+A1:2016
Acidity	-	
Dangerous substance	None	

This declaration of performance is issued under the responsibility of the identified manufacturer.

Eng. Ayman Elkholy Technical Director